





Product Type: Screw terminal

## Product Name: TU2.5-2-PE

Product Description: Connection method: Screw connection, IEC Rated current: /, IEC Rated Voltage: 1000V, Number of connections: 2, Number of levels : 1, Rated cross section: 26-12AWG

### Product Size



### Parameters

|                         |            |
|-------------------------|------------|
| ☞ SUPU ID               | TU2.5-2-PE |
| ☞ Width                 | 5.2mm      |
| ☞ Number of levels      | 1          |
| ☞ Number of connections | 2          |

|                                            |                  |
|--------------------------------------------|------------------|
| ☞ Connection method                        | Screw connection |
| ☞ Protection Level                         | IP20             |
| ☞ Insulation material                      | PA66             |
| ☞ Insulation material group                | I                |
| ☞ Contact material                         | Copper alloy     |
| ☞ Contact plating                          | Sn,Plated        |
| ☞ Ambient temperature (operation)          | -40°C~105°C      |
| ☞ Ambient temperature (assembly)           | -5°C~70°C        |
| ☞ Ambient temperature (storage)            | -25°C~60°C       |
| ☞ Permissible humidity (storage/transport) | 30%~70%          |
| ☞ Product type                             | Ground terminal  |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | /                      |
| ☞ IEC Rated Voltage                             | 1000V                  |
| ☞ Overvoltage category                          | III                    |
| ☞ Degree of pollution                           | 3                      |
| ☞ Rated impulse voltage                         | 8kV                    |
| ☞ UL Rated Current                              | /                      |
| ☞ UL Rated Voltage                              | 600V                   |
| ☞ Conductor cross section rigid                 | 0.2-4mm <sup>2</sup>   |
| ☞ Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-2.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | M2.5                   |

|                             |          |
|-----------------------------|----------|
| ☞ Locking screw torque      | 0.4N.m   |
| ☞ Fixed Screw Specification | /        |
| ☞ 固定螺钉扭矩                    | /        |
| ☞ Stripping length          | 9-11mm   |
| ☞ Use group                 | B/C      |
| ☞ Rated cross section       | 26-12AWG |
| ☞ UL Rated Current          | /        |
| ☞ UL Rated Current          | 600V     |

## Commercial data

|            |            |
|------------|------------|
| ☞ Order No | TU2.5-2-PE |
|------------|------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



---

Date:2026-03-14 05:47

The right to modify data belongs to SUPU.