

Product Type: Fixed terminal


Product Name:MC-DTD5.0H12C-0001

Product Description: Pitch:5mm Rated

Voltage : 400V Rated Current:24A Connection

method : Screw connection colour : customizable

## Product Size



## Parameters

|   |                    |
|---|--------------------|
| <input checked="" type="checkbox"/> SUPU ID               | MC-DTD5.0H12C-0001 |
| <input checked="" type="checkbox"/> Pitch                 | 5                  |
| <input checked="" type="checkbox"/> Number of levels      | Single layer       |
| <input checked="" type="checkbox"/> Number of connections | 12                 |

|   |                                  |
|---|----------------------------------|
| <input checked="" type="checkbox"/> Connection method           | Screw connection                 |
| <input checked="" type="checkbox"/> Protection Level            | IP20                             |
| <input checked="" type="checkbox"/> Operating temperature range | -40~+105°C                       |
| <input checked="" type="checkbox"/> Insulation material         | PA66                             |
| <input checked="" type="checkbox"/> Insulation material group   | I                                |
| <input checked="" type="checkbox"/> Contact material            | Copper alloy                     |
| <input checked="" type="checkbox"/> Contact plating             | Sn,Plated                        |
| <input checked="" type="checkbox"/> Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|   |                        |
|---|------------------------|
| <input checked="" type="checkbox"/> IEC Rated Current                             | 24A                    |
| <input checked="" type="checkbox"/> IEC Rated Voltage                             | 400V                   |
| <input checked="" type="checkbox"/> Overvoltage category                          | III/III/ II            |
| <input checked="" type="checkbox"/> Degree of pollution                           | 3 2 2                  |
| <input checked="" type="checkbox"/> Rated impulse voltage                         | 4.0KV 4.0KV 4.0KV      |
| <input checked="" type="checkbox"/> UL Rated Current                              | 20A - 10A              |
| <input checked="" type="checkbox"/> UL Rated Voltage                              | 300V - 300V            |
| <input checked="" type="checkbox"/> Conductor cross section rigid                 | 0.2-2.5mm <sup>2</sup> |
| <input checked="" type="checkbox"/> Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup> |
| <input checked="" type="checkbox"/> Conductor cross section flexible,with ferrule | 0.2-2.5mm <sup>2</sup> |
| <input checked="" type="checkbox"/> Locking screw Specification                   | M3                     |
| <input checked="" type="checkbox"/> Locking screw torque                          | 0.5N                   |
| <input checked="" type="checkbox"/> Fixed Screw Specification                     | -                      |
| <input checked="" type="checkbox"/> Stripping length                              | 7-8mm                  |

☒ Order No

MC-DTD5.0H12C-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat