


Product Type: Plug-in terminal-Plug

Product Name:MC-ROX7.5H10P-0001

Product Description: Pitch:7.5mm Rated Voltage : 630V Rated Current:15A Connection method : Spring cage connection colour : customizable

Product Size



Parameters

| | |
|-------------------------|--------------------|
| ⌘ SUPU ID | MC-ROX7.5H10P-0001 |
| ⌘ Pitch | 7.5 |
| ⌘ Number of levels | single layer |
| ⌘ Number of connections | 10 |

| | |
|-------------------------------|----------------------------------|
| ☞ Connection method | Spring cage connection |
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PBT |
| ☞ Insulation material group | IIIa |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Sn,Plated gold |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|---|------------------------|
| ☞ IEC Rated Current | 15A |
| ☞ IEC Rated Voltage | 630V |
| ☞ Overvoltage category | III/III/ II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 6.0KV6.0KV6.0KV |
| ☞ UL Rated Current | 15A 15A 15A |
| ☞ UL Rated Voltage | 300V 300V 300V |
| ☞ Conductor cross section rigid | 0.2-2.5mm ² |
| ☞ Conductor cross section flexible | 0.2-2.5mm ² |
| ☞ Conductor cross section flexible,with ferrule | 0.2-2.5mm ² |
| ☞ Locking screw Specification | - |
| ☞ Locking screw torque | - |
| ☞ Fixed Screw Specification | - |
| ☞ 固定螺钉扭矩 | - |

| | |
|-----------------------|----------|
| ☞ Stripping length | 9-10mm |
| ☞ Use group | B/C/D |
| ☞ Rated cross section | 24~12AWG |

Commercial data

| | |
|------------|--------------------|
| ☞ Order No | MC-ROX7.5H10P-0001 |
|------------|--------------------|

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat