



Product Type: Plug-in terminal-Plug

Product Name:MC-
RU3.81SH06-F-0001

Product Description: Pitch:3.81mm Rated
Voltage : 160V Rated Current:8A
colour : customizable



Product Size



Parameters

 SUPU ID	MC-RU3.81SH06-F-0001
 Pitch	3.81
 Number of levels	single layer
 Number of connections	6

☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	8A
☞ IEC Rated Voltage	160V
☞ Overvoltage category	III/III/ II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	2.5KV2.5KV2.5KV
☞ UL Rated Current	8A - 8A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	M2.5
☞ 固定螺钉扭矩	0.3N.M

☞ Stripping length	-
☞ Use group	B/C/D
☞ Rated cross section	-

Commercial data	
☞ Order No	MC-RU3.81SH06-F-0001

Ningbo SUPU Electronics Co., Ltd.
 Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
 Cixi City, Zhejiang Province, China
 Zip code: 315303
 Switchboard: +86 574-63288158
 Fax: +86 574-63288170
 E-mail:supucontact@supu.cn
 Service Hotline: 400-626-6336



Wechat